

# Safe and Reliable Public Access

## Commercial Vertical Platform Lifts



 **BRUNO**<sup>®</sup>  
for your independence





## Commercial Vertical Platform Lifts

### VPL-3300B Series

For 30 years, Bruno has provided accessibility solutions for people challenged by limited mobility. Safety and dependability are hallmarks of the Bruno name, and all Bruno vertical platform lifts (VPLs) are made in the USA and suitable for indoors or outdoors. Bruno's VPL-3300B series wheelchair lift includes four effective solutions for Americans with Disabilities Act (ADA) compliance in churches, schools or businesses:

- Enclosed
- Unenclosed
- 3-Gate (Toe guard)
- Shaftway/Hoistway

All Bruno VPLs are designed in accordance with ASME A18.1, section 2 and can be used in some applications to meet ANSI A117.1 National Accessibility Guidelines.



**ENCLOSED** *(pictured top right)*

Bruno's enclosed vertical platform lift is self-contained, lightweight and easy to install — no hoistway/shaftway construction needed. Aesthetically-pleasing with full size Plexiglass door and panel inserts, Bruno's enclosed vertical platform wheelchair lift combines an attractive design, dependable performance and ADA compliance. Access up to 14ft.

**3-GATE (TOE GUARD)** *(pictured top left)*

The 3-gate (toe guard) lower enclosure system provides a full barrier at the lower landing with no access under the lift for maximum safety. Like all Bruno VPLs, the 3-gate is driven by a reliable, quiet ACME screw-driven DC motor with full-time battery operation for access even during power outages. Access up to 4ft.

**UNENCLOSED** *(pictured lower right)*

The unenclosed vertical platform lift is an affordable, space saving solution for ADA compliance that is often used for providing access to stages, porches or short distances. Check to ensure a standard unenclosed platform lift is allowable under local code. Access up to 60 inches.

**SHAFTWAY/HOISTWAY** *(not pictured)*

Bruno's shaftway VPL is placed inside a shaftway (also known as a hoistway) built by others. The shaftway VPL includes a drive mast, passenger platform, doors and gates. Access up to 14ft.

ASME A18.1 requires any VPL over 60" to be enclosed.

**Learn more at [www.bruno.com](http://www.bruno.com)**



# Features and Options



## Standard features

- Access up to 14'
- Keyed, constant pressure rocker switch control on platform
- Emergency stop switch and audio/visual alarm
- Top and bottom limit switches
- Bottom platform safety panel
- 42" (1067 mm) high, solid, side platform walls
- 36" x 54" (914 mm x 1372 mm) non-skid platform
- Automatic folding ramp (unenclosed unit only)
- Fixed ramp (enclosed and 3-gate — no pit)
- 750 lb (340 kg) lifting capacity
- Reliable, quiet ACME screw-driven DC motor with full-time battery operation offers access even in a power outage — Models VPL-3353B & VPL-3375B 1/2 hp DC motor (includes 17AH batteries); models VPL-3310B, VPL-3312B, and VPL-3314B 1hp DC motor (includes 34 AH batteries)
- Gold Warranty: Two years on major components; one year on parts

## Options

- Top landing gate includes call/send controls with key and mechanical or electrical interlock
- Cold Weather Package, tested to improve performance. (recommended if operating temperature is below 20°F/-7°C)
- Several platform sizes and configurations
- Rocker switch or paddle controls on the platform
- Rocker switch or paddle landing controls
- Flush mount doors with interlock
- Power assisted door/gate operator
- ADA compliant telephone kit
- Platform gate (unenclosed application)
- Plexiglass panels: clear or bronze
- Secondary grab rail



**Bruno Independent Living Aids, Inc.**  
1780 Executive Drive, Oconomowoc, WI 53066  
[www.bruno.com](http://www.bruno.com)

© Bruno Independent Living Aids, Inc. 2016

2016-01-27 Commercial-VPL1 | MKT-CVPL-TT